




**Features**

- Aluminium housing with silicone potting
- IP67 rated and UV resistant
- DMX512 control system


**Highlights**

- Optional transparent dome cover or milky dome cover
- Fully-customizable solution for creative and demanding media projects
- Flexible mounting capability for challenging surfaces
- Field installation friendly and cost effective

**Technical Drawing**



**Accessories - Dome Cover**



**Technical Specifications**

Article Number	AC-AZ8-DA-BAMJY0	AC-AZ8-DA-BA2JY0
<b>Optical</b>		
LED	SMD LED	SMD LED
Field angle	Vertical 120° Horizontal 120°	Vertical 120° Horizontal 120°
Color	3000K	RGBW
CRI	90	90
Pitch range	50 - 5000 mm	50 - 5000 mm
<b>Environmental</b>		
Operating temperature	-35°C - 45°C	-35°C - 45°C
Operating humidity range	0 - 90% RH	0 - 90% RH
Ingress protection	IP67	IP67
LED lifetime	50,000 hrs	50,000 hrs
<b>Power</b>		
Mains input	24VDC	24VDC
Power consumption maximum	5W max	5W max
Power consumption typical	4W	4W
<b>Physical</b>		
Housing color	Aluminium	Aluminium
Lens	Milky / Transparent dome cover	Milky / Transparent dome cover
<b>Control</b>		
Control system	DMX512	DMX512