

# LED WEATHER-PROOF FITTING MARINE-T ECO

The new weather proof range of light battens are an ideal solution for indoor and outdoor applications. The solid exterior and high transmittance, low glare diffuser provides great performance and light distribution for all kind of applications. It is suitable for ceiling, wall and suspension mounting.

## AREAS OF APPLICATION:


- Airport, Transit terminal
- Direct replacement for batten luminaires with fluorescent lamps
- Wide spectrum of applications
- Factory, assembly lines
- Hypermarkets
- Warehouses
- Carpark
- Clean room (Class 100 - 100K)



## HIGHLIGHTS

- LED Light Source (Osram/Samsung/Epistar)
- LED Life Span at 50K Hours (L70B50)
- Dimmable (0-10V & DALI) function is optional
- Instant-on light
- Easy installation and maintenance
- Complies with IEC 60598
- IP65 & IK06


## RADIATION PATTERN



## CERTIFICATIONS

- CE
- RoHS

## TECHNICAL DRAWING



## TECHNICAL SPECIFICATIONS

System Power	CCT	Beam Angle	Light Output	Optics	CRI	Dimmable	Dimensions (A x B x C mm)	Voltage	Art.-No.
20W	3000/4000/6500K	120°	2400lm	Frosted	>80	NON-DIMMABLE	600 x 65 x 51	220-240V	HF-W2-DTF-TxAHCA
40W	3000/4000/6500K	120°	4800lm	Frosted	>80	NON-DIMMABLE	1200 x 65 x 51	220-240V	HF-W2-FTH-TxAHCA
50W	3000/4000/6500K	120°	6000lm	Frosted	>80	NON-DIMMABLE	1500 x 65 x 51	220-240V	HF-W2-GTR-TxAHCA

### Option:

- x : Colour
- M= 3000K
- H= 4000K
- N= 6500K

### Note :

All measurement datas are subjected to 10% tolerance due to measurement equipment tolerance and accuracy  
Lumen maintenance factor : L70B50 @ normal room temperature (25 degree C)  
All product specifications are subject to change without prior notice