

LED WEATHER-PROOF DOWNLIGHT PASKA

LED DOWNLIGHT PASKA comes with aluminum diecasting housing design, with the availabilities of few version of reflector design, enable customers to choose the light fitting appearance with their preference.

Downlight PASKA is designed to spread out evenly and smoothly down the wall with high lumen output, creating the perfect glare-less lighting effect. It provides high efficiency optics and light pattern that is suitable in any commercial application.

FEATURES

- System Power : 12W, 22W 32W & 42W
- Beam Angles : 45° & 55°
- CCT: 3000K , 4000K & 6500K
- CRI : >90
- IP rating : IP65
- Dimming : 0-10v / DALI (optional)

HIGHLIGHTS


- Easy Installation and maintenance
- LED Light Source: CREE / OSRAM / CITIZEN
- Average rated lifespan of 50,000 hours
- Flickering free
- Instant-On Light

CERTIFICATIONS

- CE
- RoHS





TECHNICAL DRAWING



Tolerance: ±2.5mm

RADIATION PATTERNS





TECHNICAL SPECIFICATIONS

System Power	ССТ	Beam Angles	Light Output	CRI	Dimension A X B (mm)	Reflector	Article Number
12W	3000/4000/6500K	45°	1200 lm	>90	75 x Ø100	Mirror	HC-DM-PHN-NxFyDL
22W	3000/4000/6500K	45°	1500 lm	>90	90 x Ø140	Mirror	HC-DM-ccU-N <mark>x</mark> FyDL
32W	3000/4000/6500K	45°	2500 lm	>90	112 x Ø185	Mirror	HC-DM-dK6-N <mark>x</mark> FyDL
42W	3000/4000/6500K	55°	3500lm	>90	128 x Ø230	Mirror	HC-DM-Mj9-NxFyDL

Option : x : CCT C=3000K D=4000K a=6500K y : Beam Angle J=45° V=55°